

MULTI-PURPOSE PIPELINE CONNECTION PATCHING



MODEL1:JKF-S
(the multi-purpose Ordinary type)



MODEL2:JKF-L
(the multi-purpose Lengthen type)



MODEL3:JKR-S
(ring with the Ordinary type)



MODEL4:JKR-L
(ring with the Lengthen type)



MODEL5:JKH-S
(the Folding Ordinary type)



MODEL6:JKH-L
(the Folding Lengthen type)



MODEL7:JKD-S
(the Dual cassette Ordinary type)



MODEL8:JKD-L
(the Dual cassette Lengthen type)



NO.	Components	Material
1	Outer casing	SUS 304,316,201
2	Rubber sealing cylinder	EPDM/NBR
3	Components stopper	SUS 304,316,201
4	Pole	SUS304,S45C SUS304,or S45C Carbon steel
5	Bolt pole	SUS304,S45C SUS304,or S45C Carbon steel
6	Screwed pole	SUS304,SCM435 MOL YBUDEN,SUS410
7	Ring	SUS304-H,SUS301-H



Technical parameter																		
Model Size	1	2	3	4	5	6	7	8	Diameter O.D (mm)	OD Range (mm)	Length (mm)		Max expand(mm)		Distance(mm)		Working Pressure Kpa	Preload (kgf.cm)
	JKF-S	JKF-L	JKR-S	JKR-L	JKH-S	JKH-L	JKD-S	JKD-L			Ordinary	Lengthen	Ordinary	Lengthen	Ordinary	Lengthen		
15					★				21.7	21-23	57	100	30	70	15±10	30±25	2500	50-80
20					★				27.2	26-28	57	100	30	70	15±10	30±25	2500	50-80
25					★				34	33-35	57	100	30	70	15±10	30±25	2500	50-80
32	★				★				42	42-44	57	100	30	70	15±10	30±25	2500	50-80
40	★	★			★	★			48.6	47-49	57	100	30	70	15±10	30±25	2500	50-80
50	★	★	★	★	★	★	★		60	59-62	80	139	46	99	20±15	45±40	2500	100-150
65	★	★	★	★	★	★	★		76	75-78	80	139	46	99	20±15	45±40	2500	100-150
80	★	★	★	★	★	★	★		89	88-92	107	203	65	138	25±20	60±55	1600	150-200
100	★	★	★	★	★	★	★		108/114	106-117	107	203	65	138	25±20	60±55	1600	150-200
125	★	★	★	★	★	★	★		140	137-143	116	204	69	150	30±25	60±55	1600	250-300
150	★	★	★	★	★	★	★		159/168	157-170	116	204	69	150	30±25	60±55	1600	250-300
200	★	★	★	★	★	★	★		219	217-221	155	255	80	150	30±25	60±55	1200	400-800
250	★	★	★	★	★	★	★		273	271-275	155	255	80	150	30±25	60±55	1200	400-800
300	★	★	★	★	★	★	★		325	323-327	155	255	80	150	30±25	60±55	1000	800-1200
350			★	★			★		377	375-380	155	255	80	150	30±25	60±55	1000	800-1200
400							★		426	424-428	155	255	80	170	30±25	60±55	800	800-1200
450							★		480	476-484	155	255	80	170	30±25	60±55	800	800-1200
500							★		530	526-534	155	255	80	170	30±25	60±55	800	1200-1500

Remark: items marked ★ are available

Our company may defer to the customer request ordering standard or other non-sing caliber product. If demand caliber in 500 above products, please directly to factory claim reference